

# → 3105 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bag is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 12" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy chain drive and dust-proof gear box housing | high quality wooden cabinet mounted on casters | pull-out bag frame mechanism mounted on rollers for easy replacement of disposable shred bags (SMC model equipped with 26 gallon shred bin) | 48 gallon shred volume (approximate)

Dimensions (D x W x H): 23 x 22 x 40 inches, Shipping weight: 324 lbs.









## CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator monitors capacity levels during operation.

#### → 3105 STRIP-CUT

Strip width	1/4"
Sheet capacity	50-52*
Security level	2
Feed opening	12''
Max. horsepower	2 1/8

#### → 3105 CROSS-CUT

Particle size	3/16" x 1 ½"
Sheet capacity	30-32*
Security level	3
Feed opening	12"

### Max. horsepower 2 ⅓ → 3105 CROSS-CUT

Particle size	3/32" x 5/8"
Sheet capacity	18-20*
Security level	4
Feed opening	12"
Max. horsepower	2 1/8

#### → 3105 SMC HIGH SECURITY

Particle size	1/32" x 3/16"
Sheet capacity	12-16*
Security level	6
Feed opening	12"
Max. horsepower	2 1/8

<sup>\*</sup> may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 9/2009.



20 amp. dedicated line required



3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com



1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com Dealer: